



PART #

20200

PRODUCT DESCRIPTION & TECHNICAL INFORMATION

16" x 1500', 33ga Hexfilm Fortress Prestretch Blown Hand Film, 4 Rolls/CS, 48 CS/Skd

Premium grade, pre-stretched hand film made with a proprietary orientation process that produces stronger films, at thinner gauges. Core extensions and ultra lightweight rolls are easy to handle and reduce operator fatigue.

APPLICATIONS

Cold environments, Grocery warehouse, Internal wrapping, Boxed products, Food processing, All load profiles.

FILM PROPERTIES	VALUE	TOLERANCE
TENSILE STRENGTH AT YIELD MD	No Yield	± 15%
TENSILE STRENGTH AT YIELD TD	1000 psi	± 15%
TENSILE STRENGTH AT BREAK MD	15000 psi	± 15%
TENSILE STRENGTH AT BREAK TD	4000 psi	± 15%
ELONGATION AT BREAK MD	180%	± 15%
ELONGATION AT BREAK TD	690%	± 15%
PROTRUSION PUNCTURE	5.3 lbs	± 15%
PROTRUSION PUNCTURE ENERGY	12.5 in-lb	± 15%
ELMENDORF TEAR STRENGTH MD	450 g/mil	± 15%
ELMENDORF TEAR STRENGTH TD	980 g/mil	± 15%
CLING - OUTSIDE TO INSIDE @ 225%	min 150 g/in	± 15%

DIMENSIONS	VALUE	TOLERANCE
CORE ID	3.05 inches	± 0.05 in
FILM THICKNESS	8.4 micron	



844-4BENCHMARK
BENCHMARKING.COM

COLUMBUS DAYTON
CLEVELAND CINCINNATI