



PART #

20008

PRODUCT DESCRIPTION & TECHNICAL INFORMATION

20" x 7500', 60ga, Hexfilm Defender Cast Machine Film, 40 Rolls/Skd

General purpose cast machine film with high strength, puncture resistance, cling, and clear optics.

APPLICATIONS

Intended primarily for pallet wrap. High Volume, Lower speed wrapping. Two-sided Cling

FILM PROPERTIES	VALUE	TOLERANCE
TENSILE STRENGTH AT YIELD MD	1250 psi	± 15%
TENSILE STRENGTH AT YIELD TD	1200 psi	± 15%
TENSILE STRENGTH AT BREAK MD	6800 psi	± 15%
TENSILE STRENGTH AT BREAK TD	4100 psi	± 15%
ELONGATION AT BREAK MD	390%	± 15%
ELONGATION AT BREAK TD	610%	± 15%
PROTRUSION PUNCTURE	9.5 lbs	± 15%
PROTRUSION PUNCTURE ENERGY	18.0 in-lb	± 15%
ELMENDORF TEAR STRENGTH MD	330 g/mil	± 15%
ELMENDORF TEAR STRENGTH TD	630 g/mil	± 15%
CLING - OUTSIDE TO INSIDE @ 225%	min 150 g/in	± 15%

DIMENSIONS	VALUE	TOLERANCE
CORE ID	3.05 inches	± 0.05 in
FILM THICKNESS	15.2 micron	



844-4BENCHMARK
BENCHMARKING.COM

COLUMBUS DAYTON
CLEVELAND CINCINNATI